¥ 96″ X 48″ FREEWAY/EXPRESSWAY

*** 60" X 36" CONVENTIONAL ROADS ≥ 45 MPH *** 42" X 30" CONVENTIONAL ROADS ≤ 40 MPH

FINES DOUBLE SIGN


_		 *	**
В/О	WORK ZONE	4″C 6″″C 8″	2 " 3 ",C
B/W	SPEED LIMIT	8 " 8 "E 6 " 8 "E 6 "	4"E 2" 4"E 2"
D /W	$\times \times$	16"E	10″E
B/W	FINES DOUBLE	4 " 6 "E 4 " 6 "E 4 "	2"E 2"E 2"E 2"

* 48" X 96" FREEWAY/EXPRESSWAY

** 24" X 48" CONVENTIONAL ROADS

SEE NOTE 7

FINES DOUBLE SPEED LIMIT ASSEMBLY




END ROAD WORK INFORMATION SIGN

* 84" X 60" FREEWAY/EXPRESSWAY

** 60" X 48" CONVENTIONAL ROADS ≥ 45 MPH

*** 42" X 36" CONVENTIONAL ROADS ≤ 40 MPH XXX CONTRACTOR'S PHONE NUMBER

NO INTERNET OR EMAIL ADDRESSES



SEE NOTE 8


* SEE TABLE 1 FOR WIDTH

EXIT RAMP SIGNING

B/O XXX EXIT NUMBER

EXIT RAMP SIGN								
NUMBER OF DIGITS	А							
Χ	72″							
XX	90″							
XXX	108″							

TABLE 1



FLAGGER STOP/SLOW PADDLE

NOTES:

- 1. USE THE POSTED SPEED LIMIT PRIOR TO WORK ZONE TO COMPUTE THE SIGN SPACING, TAPER LENGTH, BUFFER ZONE, AND WORK/CONSTRUCTION CLEAR ZONE DISTANCE, USE THE POSTED SPEED LIMIT DURING WORK TO DETERMINE THE TANGENT SPACING FOR CHANNELIZING DEVICES.
- 2. USE A 12 INCH MINIMUM MOUNTING HEIGHT TO THE BOTTOM OF THE LOWEST SIGN FOR SIGN ON PORTABLE STANDS.
- 3. USE SANDBAGS WITH SAND OR OTHER COMPARABLE SOFT MATERIAL AS BALLAST. DO NOT PLACE BALLAST HIGHER THAN 12 INCHES ABOVE THE ROADWAY AND DO NOT COVER ANY REFLECTIVE AREA OF RAILS OR SIGNS.
- 4. USE A 36 INCH MINIMUM MOUNTING HEIGHT TO THE BOTTOM OF THE LOWEST SIGN FOR SIGNS ON PORTABLE STANDS PLACED AMONG CHANNELIZING DEVICES.
- 5. SIGNS ON PORTABLE SUPPORTS MAY ONLY BE USED FOR 7 DAYS OR LESS. USE PERMANENTLY MOUNTED SIGNS FOR LONGER THAN 7 DAYS UNLESS USE OF PORTABLE SIGN SUPPORTS RECEIVES APPROVAL FROM THE REGION TRAFFIC ENGINEER.
- 6. USE A MINIMUM 7 FEET MOUNTING HEIGHT FROM ROADWAY SURFACE FOR SIGNS USING POST TYPES P1, P2 OR P3. REFER TO SN SERIES STANDARD DRAWINGS.
- 7. SIGN MAY BE USED ANYTIME IN WORK ZONE FOR SUPPLEMENTAL NOTIFICATION OF THE WORK ZONE SPEED LIMITS.
- 8. LOCATE A TEMPORARY EXIT SIGN IN THE TEMPORARY GORE. MOUNT THE TEMPORARY EXIT SIGN A MINIMUM OF 7 FEET FROM THE PAVEMENT SURFACE TO THE BOTTOM OF THE SIGN FOR BETTER VISIBILITY.

SUPPLEMENTAL DRAWING

REVISIONS	1 04/26/07 JL NEW DRAWING.							NO DATE APPR
LOTT ATTOCOL ATT TO THE LANGE CASE IN THE	UIAH UETAKIMENI UF IKANSPUKIAIIUN	STANDARD BRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION	SALT LAKERSCHOOL	RECOMMENDED FOR APPROVAL	APR.26,2007	CHAIRMAN STANDAFOS COMMITTIE	APR.26.2007	

WORK ZONE SPECIALITY SIGNS

STD DWG

TC 3D